

## 3 Ply Invoice Paper Roll Slitting

### Rewinding Machine



3Ply Invoice Paper Roll Slitting Rewinding machine adopts Simens PLC Touch screen for premium quality standard.

This machine can make the 1ply,2ply,3ply of different paper roll products,includes carbonless paper roll,NCR roll,POS roll,ATM roll etc.It is multi-funcitonal machine for different purpose of paper converting.

#### **Brief Porfile:**

Machine adopts Siemens PLC HMI for programmer to control system,include LCD color touch screen, all the automation working condition are displayed on the LCD for very simple operation.



## JIAXING PPD PACKAGING MACHINERY CO LTD

www.rewindingmachinery.com E-mail: eng@rewindingmachinery.com

Tel: +86-573-82571515 Whatsapp/Wechat: 0086 137 3685 9272

The main motor adopts Siemens inverter motor, and frequency inverter control.

Machine designed with automatic chain loading system for jumbo roll with individual motor control

All the rollers have been precise dynamic static balance treated

Machine design with end mark line marking system, printing the color line at the end of paper rolls to alarm to replace paper roll.

Machine designed with cycle knife cutting system and with automatic wastage edge trimming system.

It adopts auto tension for adjust the tension to control the roll tight or loosen as buyer option

It adopts wastage collection system with fan to blow the waste to side of the machine to collect.

With precise automatic meter counter wheel, when it reach setting length, the machine automatic stop.

Machine with working light on the top of rewinding area to more bright of rewinding area.

It equipped with emergency switch.bearing house to protect for CE certificate standard.

### Main data:

Model Number:PPD-3Y800

Max. Parent Roll Web Width:800mm

Max Parent Roll Web Diameter:1000mm

Max. Rewinding Roll Diameter:180mm

Minimum Slit Roll Width:25mm

Max Machine Speed:168meter/minute

Unwinding Roll Shaft:76mm/3" Air Shaft

Rewinding Roll Shaft:12.7/16/25mm or (or as request)

Gross Weight:1500kg Overall Dimensions:2500x1700x1500mm LWH

